

DATA SHEET

RUNPO 5

strap without Box

Item no.: 20240 | 20241 | 20242



DATA			
ITEM NO.	20240	20241	20242
LENGTH	20 m	30 m	40 m
TOTAL WEIGHT	0,46 kg	0,66 kg	0,86 kg
DIMENSION	35x500x500	45x500x500	55x500x500
MATERIAL	triple twisted special plastic tape		
Ø STAB	5,3 mm		
BENDING RADIUS	15 mm		
TOTAL BREAKING LOAD	270 kg		
TUBE DIAMETER	for pipe dimension 16 mm -40 mm		
EAN-Code	9120045472820	9120045472837	9120045472844

ADVANTAGES

- ✓ 50% less frictional resistance
- ✓ 270 kg Total breaking load
- ✓ Virtually break-free even with the tightest radii
- ✓ Advantages compared to glass fibre rod
no buckling, sticking => time savings
- ✓ Guide tip (RUNPOGLEITER) with integrated twist compensation
- ✓ 2 RUNPOGLEITER with twist compensation at the start and end of the spiral

DESCRIPTION

The RUNPO5 is another innovation by RUNPOTEC and a genuine „all-rounder“. The patented viewfinder tip, the RUNPOGLEITER with twist compensation allows even the tightest radii to be overcome, with a total breaking load of an incredible 270 kg in relation to the entire pulling system. The special plastic strap with a diameter of 5.3 mm and a triple twist has an even better shearing effect than the 3 mm glass fibre rod; the frictional resistance is only half the normal value due to spot contact. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free. The RUNPO5 can be stored in a very practical box in lengths of 20 m and 30 m. The 40 m RUNPO5 strap cannot be stored in the box.

Optimal field of application: for pipe dimensions 16 mm - 40 mm.
Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.
Scope of delivery: RUNPO5 strap without plastic box - all RUNPO 5s are delivered from the factory with 2 x RUNPOGLEITER with twist compensation at the beginning and end of the spiral.

INFORMATION

Compatible accessories:

RUNPO5 empty box
30146

RUNPO Z
 Ø 4 - 6 mm - 20272
 Ø 6 - 9 mm - 20273
 Ø 9 - 15 mm - 20274