

RP5 + XB 300 - Multi-Set

Cable roller system - stowed in RUNPOTEC system case

Item no.: 10171





VIDEO
XB 300
Click here Video



Detailed image:



Advantages RP5:
Very narrow bending radius



Detailed info see page 3

Application images:
XB 300 with cable + drum



Click here Productinformation

Description: XB 300 see Page 2
Description: RP5 see Page 3

DATA

ITEM NO.:	10171
DIMENSION	L 437 mm x W 405 mm x H 137 mm
WEIGHT	5,19 kg
DIMENSION Ø	XB 300 - 300 mm Multifunction mandrel: Ø 430 mm
LOAD CAPACITY XB 300	300 kg
TOTAL BREAKING LOAD RP5	270 kg
EAN-CODE	9 120045476552

DESCRIPTION

The multifunction mandrel has been specially developed for XB 300, XB 500 and XB 500 T cable rolling systems. Loose cable bundles can also be rolled by attaching them to the stainless-steel center mandrel and then folding out the 4 side brackets. The telescopic center mandrel measures 72 mm in diameter. It is therefore also ideal for rolling a thinner cable bundle with a small inner diameter or individual wires. The normal height of the multifunction mandrel is 196 mm, which can be extended up to max. 294 mm via the telescopic mechanism. This means high cable bundles or corresponding tube bundles can also be rolled. When the 4 side brackets are unfolded, there is a total contact surface of 430 mm in diameter. Ideally, this should correspond to the respective cable or tube bundle. A designated opening allows the unit to be combined with the RUNPOSTICKS.

Optimum area of application: : **XB300**: Rolling of (damaged) drums up to 300 kg as well as loose cable bundles or individual wires up to a max. height of 294 mm and a max. diameter of 430 mm, **RP5**: for pipe dimension 16 mm – 40 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x XB 300, 1 x Multifunction mandrel, 1 x RP5 – 30 m, 1 x RUNPOTEC system case

ADVANTAGES

- XB 300 Cable Roller
- Universal cable drum rewinder and unwinder
- Compact - lightweight
- Loadable up to 300 kg
- Excellent for damaged cable drums
- No cable clutter
- Non-slip and stable base

Multifunction mandrel

- Can be used in combination with XB 300, XB 500 and XB 500 T
- Allows loose cable bundles and individual wires to be rolled
- Telescopic centre mandrel, extendable up to 294 mm this allows high cable bundles or corresponding tube bundles to be accommodated

RP5 Cable pulling system

- 50 % less friction resistance
- 270 kg total breaking load
- Almost breakproof
- 2 x RG7 - guiding head with swivel Ø 7 mm
- Glide back protection

XB 300 Cable Roller

Loadable up to 300 kg

Item no.: 10137



XB Mandrel
Ø 45 mm
removable for
small drums

Possible applications

With clip system for the RM35 digital cable length measuring device

VIDEO

XB 300

Click here Video

KG 300

Click here Productinformation

DATA

ITEM NO.:	10137
DIMENSION	H 100 x Ø 290 mm
DIAMETER Ø	300 mm
LOAD BEARING CAPACITY	300 kg
DRUM WIDTH	variable
WEIGHT	1,26 kg
HEIGHT	105 mm
MANDREL Ø MM	15 mm / 45 mm
EAN-CODE	9120045475623

DESCRIPTION

The compact XB 300 Cable roller is a universal cable winder/unwinder for all small to medium cable reels. The XB 300 Cable roller impresses with its small, light and flat design, but can still be loaded up to 300 kg.

Especially suitable for damaged cable drums.

It enables trouble-free and rational working without tangled cables. 6 rubberized feet ensure a non-slip and stable base. Optimal for protecting surfaces for already finished floor coverings. Due to the removable mandrel, cable drums with different hole sizes can be used.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x XB 300 Cable roller incl. XB mandrel

ADVANTAGES

- Universal cable drum rewinder and unwinder
- For all types of cables and cable drums even with very small inner diameters
- Compact - lightweight - 1.26 kg net weight
- Loadable up to 300 kg
- Excellent for damaged cable drums
- No cable clutter
- Trouble-free and rational work approach
- Non-slip and stable base

INFORMATION

Available as spare part

Multifunction mandrel

Item no.: 20696



Click here
Produktinformation

Alternative cable roller

XB 500 Cable Roller

Item no.: 10136



Click here
Produktinformation

RUNPOSTICKS ROT

Item no.: 20881



Click here
Produktinformation

RP5 RUNPOTEC Polyester Ø 5,5 mm – without meter counter

optimal for pipe diameter 16–40 mm

Item no.: 10013 | 10014



Beginning:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Glide back protection
Aktive

Triple twisted special polyester fish tape Ø 5,5 mm

Ending:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Attention!
electric conductive

Very narrow bending radius

R = 15 mm

Virtually break-free even with tightest radii

R

50 % less friction resistance

Only punctual contact

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

Rod	Rec. pipe-Ø	Bending radius	Total breaking load incl. RG7 - RUNPOGLIDER
Ø			
5,5 mm	16 – 40 mm	15 mm	270 kg

DATA

ITEM NO.	10013	10014
LENGTH	20 m	30 m
WEIGHT	1,31 kg	1,62 kg
EAN-CODE	9120045472806	9120045472813
DIMENSION BOX	L 380 X W 310 X H 50 mm	
TOTAL BREAKING LOAD	270 kg (on the whole strap)	
ROD Ø	Ø 5,5 mm	
MATERIAL	triple twisted special polyester fish tape	
BENDING RADIUS	15 mm	
PIPE Ø	optimally from 16 mm - 40 mm	

DESCRIPTION

The RP5 - RUNPOTEC Polyester Ø 5.5 mm is a cable pulling tool without meter counter. The triple-twisted special plastic tape with a diameter of 5.5 mm has an even better shearing effect than the 3 mm fiberglass rod; the frictional resistance is only half the normal value due to spot contact. The patented RG7 guiding head with swivel Ø 5.5 mm (pressed at the beginning and end of the tape) allows overcoming tight radii (bending radius 15 mm). The RP5 Ø 5.5 mm is stored in a jobsite suitable box incl. glide back protection. The total breaking load of 270 kg refers to the entire pulling system. The cable pulling system is virtually breakage-free. The RP5 replacement strap cannot be stored in the box. **Optimal field of application:** for pipes with a diameter of Ø 16 mm - 40 mm. **Application video:** a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com. **Scope of supply:** 1 x RP5 RUNPOTEC Polyester Ø 5,5 mm without meter counter in a plastic box, including 2 x RG7 RUNPOGLIDER with swivel (pressed on both sides)

ADVANTAGES

- Total breaking load 270 kg
- 2 x RG7 - Guiding head with swivel Ø 7 mm
- Glide back protection
- Triple twisted special plastic tape Ø 5,5 mm
- 50 % less frictional resistance
- Virtually break-free, even with the tightest radii

INFORMATION

Compatible accessories:
RP5 Replacement fish tape
 20 m – Item no.: 20240
 30 m – Item no.: 20241



Cable pulling loop with hook
 (Quick release fastener) – set of 4
 Item no.: 10159

