

# DATA SHEET

## RC2 Inspectioncamera- 30m + GF3- 30m

for pipe inspection from Ø 14 mm (inside)

Item no. 11146



Scope of supply: GF3 - 30m + RC 2

Camera with reel + Monitor + case 30 m

### Included Accessories:



- A. RG7 RUNPOGLIDER with front thread
- B. Micro memory card 8 GB / adapter
- C. Connection thread set (blind cap, inside and outside connection thread)
- D. SYSTEMGLIDER RC2
- E. Fishing hook
- F. Magnet fishing-set
- G. High-performance 320-lumen rechargeable LED lamp (protection rating IP 67)
- H. Flexible attachment 12 cm
- I. USB / USB-C charging cable 1,5 m
- J. Thread attachment RC2
- K. USB charging adapter 230 V

### DATA

ITEM NO.	11146
CABLE LENGTH M	30 m
TOTAL WEIGHT KG	4,932 kg
DIMENSIONS	B 437 mm   L 405 mm   H 137 mm
MONITOR	3.5" TFT LCD Monitor 16 M color
CAMERA PROBE	307.200 Pixel (640 x 480)
ILLUMINATION	6 x LED (integrated in camera probe)
PROTECTION CLASS	IP 67 (camera probe and cable)
FIELD OF VIEW	64 °
FOCUSSING DISTANCE	30 mm – 80 mm
POWER SUPPLY	230 V o battery-operated (battery included)
LANGUAGES	DE, EN, FR, ES, PT, IT, NL, DA, SE, NO, FI, PL, CS, HU, RU, IS, LT, SK, SLO, HR, TR
EAN-CODE	9120045477177

### ADVANTAGES

- ✓ Protection class IP67
- ✓ Pipe inspection from Ø 14 mm (inside)
- ✓ Ventilation pipes, drainage pipes, sewage pipes and much more
- ✓ Also for cavity inspection and suspended ceilings
- ✓ Lengths 10 m, 30 m or 50 m
- ✓ Memory function/documented evidence  
Photo (JPG), Video (AVI), Audio
- ✓ Spool with camera cable can be easily unwound or rewound via the X BOARD series


### DESCRIPTION


**RUNPOCAM RC2 inspection camera - 30 m** with reel incl. monitor bracket. In W-Box system case - compatible with Sortimo. Extra large 3.5" TFT LCD 16M colour display, protection class IP 67, rechargeable battery operation up to 6 hours. Evidence preservation/storage function: photo, video and audio. CAMERA HEAD with 6 integrated LEDs, enclosed in robust stainless-steel head (Ø 13 mm) with RTG Ø 6 mm internal thread. Compatible with all RUNPOTEC products with RTG Ø 6 mm thread. For pipe inspection from 14 mm inner diameter (empty pipe Ø 20mm), but also for larger pipe cross-sections (ventilation systems, drainage, sewage pipes). + **GF3 - Cable pulling tool** incl. digital meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with twist. Stowed in a shock-proof plastic box. The box is splash-water and dust-proof, extremely shock-proof and therefore ideally suited for the construction site. The glide-back protection prevents the fibreglass rod from accidentally slipping back into the box. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load 130 kg  
**Optimal field of application:** for pipe dimension 10 mm - 50 mm  
**Application film:** you can watch a short, very informative application film by scanning the QR code or at [www.runpotec.com](http://www.runpotec.com)  
**Scope of supply:** 1 x RC2 inspection camera with cable 30 m incl. reel, 1 x RUNPOTEC system case, 1 x RG7 RUNPOGLIDER with front thread, 1 x system slider, 1 x rechargeable battery powered high-performance 320 lumen LED-lamp, 1 x Micro SD Card 8 GB, 1 x magnet fishing set, 1 x connecting thread set RTG Ø 6 mm (3-parts), 1 x fishing hook, 1 x flexible attachment 12 cm, 1 x USB cable 1,5 m, 1 x USB charging plug 230 V, 1 x thread attachment RC 2, 1 x GF3 with metre counter, length 30 m, 1 x guiding head with twist adjustment, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pull-in aid, 1 x special adhesive 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive sleeves Ø 3 mm, 3 x pull eyes Ø 7 mm, 1 x bulb Ø 11 mm, 1 x connecting sleeve, 2 x mounting-wrenches, 1 x battery CR2032

### INFORMATION

#### Combinable plug systems:

RP1 | Length 5 m – 30 m  [Hier klicken Produktinformationen](#)

**GLASFASERSTÄBE**  
 Ø 4,5 – 6 – 7,5 – 9 – 11 m  
 Length 30 up to 300 meter  [Hier klicken Produktinformationen](#)

**RUNPOSTICKS**  
 Paket: Comfort | Standard  
 Art.-Nr.: 10020 | 10016  [Hier klicken Produktinformationen](#)

# DATENBLATT

## GF3 Glass fiber Ø 3 mm

Cable pulling system for pipe diameter 10-50 mm

Item no.: 10192 | 10193 | 10195



**CONTENT:** Accessory box (16-parts)



**INFO:**



**Front End:** Guiding head with swivel and RTG Ø 6 mm front thread with kink-protection



**Rear end:** Kink protection with RTG Ø 6 mm inner thread

DATA			
ITEM NO.	10192	10193	10195
		Offer	
LENGTH	20 m	30 m	50 m
TOTAL WEIGHT	1,28 kg	1,38 kg	1,58 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE Ø	optimal from 10 mm - 50 mm		
DIMENSION	L: 295 mm x W: 245 mm x H: 74 mm		
EAN-CODE	9120045476729	9120045477122	9120045477139

### ADVANTAGES

- ✓ Integrated digital meter counter
- ✓ Guiding head with swivel and kink protection
- ✓ Autom. glide back protection
- ✓ Easy service access
- ✓ Extremely shockproof box
- ✓ Also for occupied pipes
- ✓ Including cable pulling loop
- ✓ Inspection camera RC2 compatible
- ✓ Total breaking load 130 kg

Rod	rec. pipe diameter	Bending radius w.e.joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	10 - 50 mm	38 mm	28 mm	450 kg	130 kg
0,118"	0,394" - 1,969"	1,102"	1,102"	992,08 lbs	286,60 lbs

### DESCRIPTION

GF3 - Cable pulling tool incl. digital meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with twist adjustment. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection prevents the fiberglass rod from accidentally slipping back into the box. Furthermore, the box has an ergonomic carrying handle and an anti-slip coating. The scope of delivery includes an 18-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection joints. The cable pulling loop (Ø 14 mm outside) with built-in twist adjustment and protective cap included can be used for one or more cables up to a cable diameter of Ø 12 mm. Any plugs are protected by tensile load on the cable.

**Optimal field of application:** for pipe dimension 10 mm - 50 mm.

**Application film:** You can watch a short, very informative application film by scanning the QR code or at [www.runpotec.com](http://www.runpotec.com).

**Scope of supply:** 1 x GF3 incl. metre counter in plastic box, kink protection ending joint on both sides (start / end), contents of the accessory box: 1 x guiding head with twist adjustment, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pull-in aid, 1 x special adhesive 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive sleeves Ø 3 mm, 3 x pull eyes Ø 7 mm, 1 x starting bulb Ø 11 mm, 1 x connecting sleeve, 2 x mounting-wrench, 1 x button battery CR2032

### INFORMATION

**Compatibel with:**

**RC2** inspection camera

Length: 10 m | 30 m | 50 m

Item no.: 10139 | 10140 | 10141



Click here Productinformation