RC 2 CAMERA PROBE WITH CABLE

incl. camera reel - cable lengths 10 m, 30 m and 50 m $\,$

Item no.: 20593 | 20560 | 20559







DATAS				
ITEM NO.	20593	20560	20559	
CABLE LENGHTS m	10 m	30 m	50 m	
WEIGHT KG	0,32 kg	0,96 kg	1,6 kg	
DIMENSION	L 267 mm x B	L 267 mm x B 177 mm x H 38 mm		
CAMERA PROBE	345.000 Pixe	345.000 Pixel (640 x 480)		
ILLUMINATION	6 x LED (inte	6 x LED (integrated in camera probe)		
PROTECTION CLASS	IP 67 (camer	IP 67 (camera probe and cable)		
FIELD OF VIEW	64 °	64°		
FOCUSSING DISTANCE	30 mm – 80 n	30 mm – 80 mm		
EAN-CODE	9120045476132	9120045476149	9120045476156	

ADVANTAGES

- ✓ Pipe inspection from Ø 14 mm (inside)
- ✓ Protection class IP67
- Wall mount Mounting bracket + magnetic holder for monitor
- Vertical monitor adjustment
 Practical viewing angle 60°, hands free for working
- ✓ Cable unwinding option

 with X BOARD cable unwinder XB 300 or

 XB 500

DESCRIPTION

CAMERA HEAD RC2 with cable incl. camera coil in the cable lengths 10 m, 30 m and 50 m. CAMERA HEAD with cable (640 x 480 pixels), protection class IP67.

CAMERA HEAD with 6 integrated LEDs enclosed in a robust stainless steel head (Ø 13 mm) with RTG Ø 6 mm thread internal thread, compatible with all RUNPOTEC products with RTG Ø 6 mm thread (POWER REX, RUNPOSTICKS, RUNPO 1, glass fibre rod Ø 4.5 - 6 - 7.5 - 9 - 11 - 15 mm).

Optimal field of application: For pipe inspections over long distances of up to 50 m. As of 14 mm inner diameter (corresponds to empty pipe Ø 20 mm), but also for larger pipe cross-sections (ventilation systems, drainage systems, sewage pipes etc.). In combination with the RUNPOSTICKS, excellent for cavity wall inspections, suspended ceilings (above high ceiling profiles), manhole and underfloor ducts, maintenance and system inspections **Application video:** a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com

Scope of delivery: camera head RC 2 with cable - incl. camera coil

INFORMATION

Use with: RUNPOCAM RC2

Length: 10 m | 30 m | 50 m Item no:10139 | 10140 | 10141

