

# DATA SHEET

## GUIDING HEAD W. KINK PROTECTION GF3

for Ø 3 mm fiberglass rod, 5-parts

Item no.: 20826



DATA	
ITEM NO.	20826
WEIGHT KG	0,0416 kg
DIMENSION	L x 100 mm x B 28 mm x H 8 mm
MATERIAL	Stainless steel
EAN-CODE	9120045477283

### ADVANTAGES

- ✓ With swivel and kink protection
- ✓ Breaking load 140 kg
- ✓ Stainless steel
- ✓ Extra large eyelet

### BESCHREIBUNG

Replacement glass fibre rod GF3 Ø 3 mm with kink protection ending joint made of stainless steel and guiding head with twist adjustment and pulling eye Ø 7 mm with RTG Ø 6 mm thread. The specified total breaking load of 130 kg always refers to the entire product (glass fibre rod incl. kink protection ending joints).

**Optimal field of application:** for pipe dimension 10 mm - 50 mm.

**Application film:** You can watch a short, very informative application film by scanning the QR code or at [www.runpotec.com](http://www.runpotec.com).

**Scope of supply:** 1 x Replacement glass fibre rod GF3 Ø 3 mm, length: 20 m, kink-protection-ending joint on both side (Beginning/ Ending), 1 x guiding head with twist adjustment, 1 x pulling eye Ø 7 mm, 2 x mounting-wrenches

### INFORMATION

#### Use with

#### Cable pulling system GF 3

Length: 20 m | 30m | 50m  
Item no. 10192 | 10193 | 10195



Click here Productinformation

#### Replacement fiberglass rod GF 3:

Length: 20 m | 30m | 50m  
Item no.: 20816 | 20817 | 20818



Click here Productinformation