

# DATA SHEET

## STARTING HEAD Ø 30 MM

for RUNPOTEC products with thread RTG Ø 12 mm

Item no.: 20404



**VIDEO**

Fibreglass rod Ø 7,5mm, 9 mm/11 mm

Click here Video

Click here Productinformation

Application images:

Can be adapted on roller, shackle, starting head Ø 20 mm, Ø 30 mm

Cross section

RTG Ø 12 mm    RTG Ø 6 mm

### DATEN

ITEM NO.	20404
TOTAL WEIGHT KG	0,205
THREAD	RTG Ø 12 mm
DIMENSION	LENGTH 54 mm - Ø 30 mm
MATERIAL	Stainless steel
EAN-CODE	9120045474398

### DESCRIPTION

Starting bulb Ø 30 mm made of stainless steel for glass fibre rod Ø 7.5 mm, 9 mm, 11 mm, 15 mm - RTG Ø 12 mm thread.

The starting bulb has an additional transition thread to RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling sleeves etc.

**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com).

**Scope of delivery:** 1 x starting bulb incl. connection thread

### ADVANTAGES

- ✓ RUNPOTEC RTG Ø 12 mm
- ✓ for guide probe or smaller cable pulling sleeves
- ✓ incl. connecting thread
- ✓ Stainless steel
- ✓ leanest head

### INFORMATION

#### RECOMMENDED PRODUCTS.

**FIBREGLASS ROD Ø 7,5 mm**  
10076/10077/10078/10079/  
10080/10091

**FIBREGLASS ROD Ø 9 mm:**  
10081/10082/10083/10084/  
10085/10086/10110

**FIBREGLASS ROD Ø 11 mm:**  
10092/10093/10094/10095/10096/  
10097

