

DATA SHEET

ROLLER Ø 50 MM

for RUNPOTEC products with thread RTG Ø 12 mm

Item no.: 20382



VIDEO

Fibreglass rod
7,5 mm, 9 mm,
11 mm

[Click here
Video](#)

[Click here
Productinformation](#)

Application images:

Solution with flexible leading head-set

Taper of through the flexible RUNPOSTICKS Ø 4,5 mm (yellow), Ø 5,5 mm (black) or Ø 7,5 mm (red). Thereby it makes it possible to get over the tight bend or radii.

Fiberglass rod Ø 7.5 mm, 9 mm or 11 mm stops at to narrow radii from of the tube

Additional manual haul support possible

Cross section:
RTG Ø 12 mm RTG Ø 6 mm

DATA	
ITEM NO.	20382
WEIGHT KG	0,195 kg
THREAD	RTG Ø 12 mm with connection thread RTG Ø 6 mm
DIMENSION	Ø 50 mm
MATERIAL	Aluminium/stainless steel
EAN-CODE	9120045474299

ADVANTAGES

- ✓ Substantially improved gliding or rolling in empty pipes
- ✓ RUNPOTEC RTG Ø 12 mm thread
- ✓ Connection thread on RTG Ø 6mm thread - to adapt guide probe
- ✓ Aluminium/stainless steel

BESCHREIBUNG

For substantially improved sliding or rolling in empty pipes.
The roller is compatible with fibreglass rod Ø 7.5 mm, 9 mm, 11 mm or 15 mm with RTG Ø 12 mm thread.
The roller has an additional connecting thread to RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling sleeves etc.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 x roller Ø 50 mm and connecting thread

INFORMATION

Recommended products:

Fiberglass rod Ø 7,5 mm
10076/10077/10078/10079/
10080/10091

Fiberglass rod Ø 9 mm:
10081/10082/10083/10084/
10085/10086/10110

Fiberglass rod Ø 11 mm:
10092/10093/10094/10095/10096/
10097

Fiberglass rod Ø 15 mm:
10099/10100/10101/10102/10103/
10104

